

Product Description:

ROCK PRIME DP is a fast curing, cost-effective, 2-component waterborne epoxy primer intended for use as a clear or field pigmented primer or concrete sealer coat. **ROCK PRIME DP** has no offensive odor, has no reportable VOC or HAPS and meets all USDA/FDA guidelines for use in federally inspected facilities.

ROCK PRIME DP can be used as a standard primer under most ROCK-TRED flooring or wall systems. It can be used as a direct to prepared concrete finish sealer where low or no topical film build is desired or as a pre-primer under other ROCK-TRED Primers/Coatings where extreme bond strength is required due to poor substrate conditions.

Physical Testing Information:

Volume mix ratio	1:4 (Resin to Hardener)
Viscosity (mixed)	30 – 50 CPS Typical
Solids Content (%)	48% (ASTM D-2697)
VOC	0 g/l (EPA method 24)
Application Temps	60° – 85°F
Gel Time (at 50% RH)	45 - 60 minutes @ 75°F
Dry to Touch	30 – 60 minutes @ 75°F
Through Cure (recoat with compatible materials)	2 - 3 hours @ 75°F
Open to light traffic	24 hours @ 75°F
Shelf Life:	1 Year in unopened units

Please review ROCK-TRED's Product Data Sheet and SDS for further information on this product. All physical testing information is from performance testing run on neat coats of the tested product unless otherwise indicated.