

**Product Description:**

The **ROCK-TRED SL (Self Leveling) System** is a 1/8" thick, 100% solids epoxy and suspended aggregate flooring system that can be installed in as few as one application step. The resulting solid color monolithic floor is extremely durable, impact resistant and has a very high compressive strength.

The **ROCK-TRED SL System** is specified for use as a high performance self-leveling flooring system in areas that require a very even self-leveling finish and may be subjected to medium to heavy traffic, heavy point and rolling loads and exposure to moderate chemical spillage.

**Physical Testing Information:**

Compressive strength	12,000 psi (ASTM C-579)
Tensile Strength	8,500 psi (ASTM D-638)
Bond strength	400+ psi (2758 kPa) w/ concrete failure (ASTM D-4541)
Impact resistance	>160 in-lbs (18.08 Nm) (ASTM D-2794)
Abrasion resistance	0.06 g (ASTM D-4060, CS-17 wheel)
Solids (by volume)	100% (ASTM D-1464)
VOC content	0 lbs/gal (0.014 kg/l) (EPA Method 24)
Water absorption	less than .2% (ASTM C-413)
Flammability rate	Self-Extinguishing (ASTM D-635)

Please review ROCK-TRED's Product Data Sheet and SDS for further information on this product. All physical testing information is from performance testing run on neat coats of the tested product unless otherwise indicated.