

Defining Excellence Since 1939

PHYSICAL TESTING DATA

RT SPORTSMAT PORE FILLER

Product Description:

RT SPORTSMAT PORE FILLER is a two-component, thixotropic, polyurethane mastic filler designed to bond to and fill the pores of ROCK-TRED SPORTSMAT rubber underlayment mats.

RT SPORTSMAT PORE FILLER is used as the grouting material over ROCK-TRED SPORTSMAT when creating ROCK-TRED SPORTSMAT Systems. Typical uses of the SPORTSMAT Systems include areas where either a decorative or solid color anti-fatigue, shock absorbing and/or impact resistant system is required.

Physical Testing Information:

 $\begin{array}{lll} \mbox{Density (at } 73^0 \mbox{ F)} & 1.26 - 1.32 \mbox{ g/cm}^3 \\ \mbox{Color} & \mbox{Gray} \\ \mbox{Volatile Organic Compounds, ASTM D-2369-81} & 0 \mbox{ gm/liter} \\ \mbox{Shore A Hardness (at } 73^0 \mbox{ F)} & 65 - 85 \end{array}$

Mix ratio (by weight)

Viscosity [mixed]

Gel Time

Dry to Touch (coat SPORTSMAT with compatible products)

Application Temps

Shelf Life

4 to 1

Highly Thixotropic

35 - 55 minutes @ 73° F

4 hours @ 73° F

50° - 100° F

1 year in unopened units

Please review ROCK-TRED's Product Data Sheet and SDS for further information on this product. All physical testing information is from performance testing run on neat coats of the tested product unless otherwise indicated.