

TECHNICAL DATA

RT SERIES 101 ROCK-POWER

LIQUID CLEANER, DEGREASER AND NEUTRALIZER

DESCRIPTION:

ROCK-POWER is a powerful liquid floor cleaner and surface degreaser. It is safe to use, clear, odorless, non-flammable and does not contain solvent, ammonia or bleach. ROCK-POWER's unique combination of water softeners and extra strength detergents provide a cleaner that can be used at concentrate straight from the container, or diluted up to 32:1 with hot, cold, hard or soft water. ROCK-POWER can also be used to help neutralize slight PH imbalances in concrete slabs.

USES:

ROCK-POWER is an effective product for cleaning polymer floor and wall coatings, polished or unpolished concrete substrates, various types of brick, marble, Formica, vinyl and porcelain. **ROCK-POWER** is ideal for cleaning and removing accumulated dirt and stains, grease, oils, many chemicals, food & beverage spills, mildew and heel marks.

ADVANTAGES:

- 2 year shelf life
- Odorless
- Economical
- Environmentally friendly
- User friendly / safe
- Non-irritating
- Can be diluted
- Can be hand applied or used in mechanical floor scrubbers

FOR BEST RESULTS:

- · Agitate contents of container before using
- DO NOT allow solution to dry on the surface
- DO NOT mix with other cleaners / products
- Thoroughly 'flush' / rinse all surfaces, tools or equipment after using this product

DILUTION RATIOS:

SURFACE	RECOMMENDED DILUTION
TRUCKS / AUTOS / METALS	4 oz. to 1 gal. of water
SEALED/COATED CONCRETE	6 oz. to 1 gal. of water
CERAMIC TILE OR MASORY	8 oz. to 1 gal. of water
HEAVY GREASE & OILS	1 pint to 1 gal. of water
PARTS CLEANING	Full Strength

PACKAGING:

- 1 gallon jug
- 5 Gallon pail
- 55 gallon drum

RT SERIES 101 - ROCK-POWER

PRODUCT USE / APPLICATION:

ROCK-POWER can be safely applied using mechanical floor scrubbers, pressure washer, used in 'dip' tanks, mops, spray bottles or rags.

Surfaces that are heavily soiled should be treated with full strength ROCK-POWER and allowed to soak for several minutes before agitating and rinsing. Stubborn stains / grease may require more than one application of **ROCK-POWER** to completely remove.

CLEAN UP:

Be sure that all application tools and equipment (including cleaning buckets, mops, scrubbers, etc.) are thoroughly rinsed and cleaned using fresh water.

DISPOSAL:

Empty product containers will contain product residue and must be disposed of properly. Label warnings must be observed at all times. All containers must be disposed in accordance with federal, state, and local regulations.

STORAGE:

DO NOT allow **ROCK-TRED** products to freeze. All **ROCK-TRED** products should be properly stored above the floor on pallets or shelves, and in an area that has a constant minimum temperature of 50°F.

IMPORTANT NOTICE:

Always read and acquaint yourself with **ROCK-TRED'S** Product Data Sheet, SDS [safety data sheet], and product labels for each individual product prior to mixing and prior to use.

For technical assistance with this product, for additional information, or situations not covered in this data sheet, please contact your Area Sales Representative or contact **ROCK-TRED** directly.

WARRANTY:

Information about ROCK-TRED products is given, to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you make your own tests to determine suitability of the product for the particular purpose. As products are often applied or used under conditions beyond our control, ROCK-TRED cannot guarantee anything except the quality of its products. ROCK-TRED warrants that the products meet the specifications set forth by ROCK-TRED, but we reserve the right to change any given specification prior to notice. ROCK-TRED DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of a ROCK-TRED product constitutes acceptance of the terms of this limited warranty and the terms and conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of the merchandise, purchaser has 30 days to notify ROCK-TRED, in writing, that materials are defective. In the event ROCK-TRED finds that the product delivered is off specification, ROCK-TRED will, at its sole discretion, either replace the product(s) or refund the purchase price thereof, and ROCK-TRED's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of ROCK-TRED exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. ROCK-TRED will, under no circumstances, be liable for special, incidental, or consequential damages. This warranty supersedes all other guaranties, whether oral or written, and whether expressed, implied, or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals that may cause serious physical injury. Before using, pl