

**90% SOLIDS, LOW ODOR POLYASPARTIC PRIMER, BODY AND FINISH COATING**

**DESCRIPTION:**

**CHEM-THANE P100** is a water clear, 2-component, 90% solids modified aliphatic / polyaspartic coating that combines the best attributes of high grade epoxy and urethane coatings. **CHEM-THANE P100** offers the highest UV resistance available, remains flexible over time and has very good abrasion and chemical resistance. **CHEM-THANE P100** is compliant with all VOC and HAPS regulations throughout the US and meets all USDA/FDA guidelines for use in federally inspected facilities.

**USES and TYPICAL COVERAGE:**

**As a BODY or FINISH coat:** **CHEM-THANE P100** is an excellent non-yellowing, body or finish coat for any ROCK-TRED floor or wall coating system. This coating is recommended for use in moderate temperature environments (40°- 70°F) that require fast return to service and/or superior UV resistance while maintaining VOC compliance. Typical coverage per coat is from 80 sq. ft. /gal. (20 mils) to 150 sq. ft. / gal. (11 mils). For a lower viscosity you may add up to 16 oz. P-100 Viscosity Reducer per mixed gallon of P-100.

**As a PRIMER coat:** **CHEM-THANE P100** can be used as a fast setting, water clear primer by adding P100 Viscosity Reducer at 10 oz. per mixed gallon of P100. Coverage will increase to approximately 200+ sq. ft. / gal. (8+ mils).

**ADVANTAGES:**

- Water clear and superior UV resistance
- Very Good chemical and abrasion resistance
- Low Odor even with Viscosity Reducer added
- Viscosity can be changed in the field per the job needs
- Single coat high build capabilities – apply at up to 20 mils per coat
- VOC compliant through the US even with Viscosity Reducer
- Easy working formula for installations between 40°- 70°F
- Can be tinted with ROCK-TRED Universal Colorants EXCEPT VELVET and LIGHT BLUE. Loading is one 1.5 Colorant Jar (1/2 BagPak of Colorant) per 3 gallon mix

**TYPICAL PROPERTIES:**

PHYSICAL PROPERTIES	
Volume mix ratio	2 to 1 (Resin to Hardener)
Viscosity (mixed)	650 CPS Typical
Solids Content (%)	90% (ASTM D-2697)
Hardness (ASTM D-2440)	55 - 60 (Shore D) @ 7 day cure
VOC	Compliant with all US Regulations
Application Temps.	40° – 70° F
Gel Time (see "Limitations" section below for more details)	60 minutes @ 75°F
Dry to Touch (recoat with compatible products)	1 hour @ 75°F
Through Cure	3.5 hours @ 75°F
Open for light traffic/use	24 hours @ 75°F
Shelf Life	1 Year in unopened units

**PACKAGING:**

- 3.0 Gallon Units
- 15 Gallon Units

# RT SERIES 500-100 CHEM-THANE P100

## LIMITATIONS & FOR BEST RESULTS:

- May be thinned with up to 16 oz. P-100 Viscosity Reducer per mixed gallon of P-100. When using as primer use a minimum of 10 oz. of Viscosity Reducer per mixed gallon of P-100. *Adding Viscosity Reducer will lower the viscosity and slightly increase the odor during cure, but will not alter the reportable VOC content. Adding Viscosity Reducer will slow the cure time, but will not change the performance characteristics of the cured material.*
- Do not apply when humidity exceeds 70%.
- Do not allow to puddle during application.
- Allow each coat to dry to 'tack-free' or clear prior to re-coat.
- When re-coating, apply the next coat within 24 hours of completing the previous coat.
- Mix on very low RPM or using a stir stick for 45-60 seconds. DO NOT INTRODUCE ANY AIR.
- When possible, squeegee on the shorter length of the room and immediately back roll in one pass in the opposite direction to strike off. Thickness of application should be controlled by the squeegee. Do not rely on back roll to eliminate puddles. Do not over back-roll as this will entrain air.
- Gel time listed above for this product should not be confused with working time – actual working time is typically 8-10 minutes at 70°F and 45% RH when no Viscosity Reducer has been added.

## PRODUCT APPLICATION:

Apply by brush, roller and squeegee. 12" squeegees are recommended to help reduce pooling. Unlike epoxy coatings P-100 has a longer pot life in the bucket and a shorter working time after it is poured onto the substrate. For best results installation crews must work closely together and pour out only enough catalyzed material that can be cut in, squeegeed and quickly back rolled before it starts to gel. Temperature and humidity will both increase how rapidly this material sets. When working on warmer or more humid job sites smaller mixes thinned with the maximum amount of Viscosity Reducer are recommended. ROCK-TRED product test data is based on environmental temperatures of 75°F. Viscosity and working time are always affected by temperatures above or below that mark. When applying product always consider the ambient, surface, and product temperature at the time and place of installation.

## COLOR AND TEXTURES:

CHEM-THANE P100 is manufactured in water clear. Using a 1.5 Jar (equal to 1/2 of one Colorant BagPak) of ROCK-TRED UNIVERSAL Colorant per 3.0 gallon mix is acceptable except for VELVET or LIGHT BLUE – do not use VELVET or LIGHT BLUE with P-100 V.2014. Most ROCK-TRED products are available in a wide range of textures using an appropriate aggregate.

## PRODUCT STORAGE:

**DO NOT** allow ROCK-TRED products to freeze. All ROCK-TRED products should be properly stored above the floor on pallets or shelves, and in an area that has a constant minimum temperature of 50°F.

## CHEMICAL RESISTANCE:

Always refer to ROCK-TRED's chemical resistance chart for specific information on each product / system or contact ROCK-TRED directly.

## SURFACE PREPARATION:

Always apply ROCK-TRED products to a clean / sound substrate that is free of laitance, grease, oils, debris and curing compounds. Make certain that concrete is properly dried and prepared before applying ROCK-TRED materials. Concrete substrates should be treated with ICP's Arizona Polymer Flooring System's Vapor Solve System when moisture testing per ASTM F2170 shows results over 80% RH. Whenever possible, remove existing coatings and/or flooring systems completely; if complete removal is not possible test to determine adhesion to the existing material. Mechanical preparation by means of shot-blasting or diamond grinding to ICRI CSP 2/3/5 is the recommended preparation method (see ICRI Guideline No. 03732 for more information). If the substrate is not properly prepared and the appropriate profile is not achieved, failure of the product to adhere to the substrate may occur.

## CLEAN UP:

Application tools and equipment can be cleaned with soap and water immediately after use or with solvent once the product has begun to cure.

## DISPOSAL:

Product containers will contain product residue and must be disposed of properly. Label warnings must be observed at all times. All containers must be disposed in accordance with federal, state, and local regulations.

## IMPORTANT NOTICE:

Always read and acquaint yourself with ROCK-TRED's Product Data Sheet, SDS [safety data sheet], and product labels for each individual product prior to mixing and prior to use. For further assistance, product questions, additional information and/or unexpected or unusual installation conditions – contact your Area Sales Representative or ROCK-TRED directly for recommendations. Kit components are pre-measured for optimal performance. Catalyzation errors due to incorrect mixing in the field voids product warranty.

**WARRANTY:** Information about ROCK-TRED products is given, to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you make your own tests to determine suitability of the product for the particular purpose. As products are often applied or used under conditions beyond our control, ROCK-TRED cannot guarantee anything except the quality of its products. ROCK-TRED warrants that the products meet the specifications set forth by ROCK-TRED, but we reserve the right to change any given specification prior to notice. ROCK-TRED DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of a ROCK-TRED product constitutes acceptance of the terms of this limited warranty and the terms and conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of the merchandise, purchaser has 30 days to notify ROCK-TRED, in writing, that materials are defective. In the event ROCK-TRED finds that the product delivered is off specification, ROCK-TRED will, at its sole discretion, either replace the product(s) or refund the purchase price thereof, and ROCK-TRED's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of ROCK-TRED exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. ROCK-TRED will, under no circumstance, be liable for special, incidental, or consequential damages. This warranty supersedes all other guarantees, whether oral or written, and whether expressed, implied, or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals that may cause serious physical injury. Before using, please read the Safety Data Sheet and follow all precautions to prevent bodily harm.